

PRESS BRAKE OPERATING PARAMETERS BY MODEL

Technical data Model	Nominal force (kN)	length of working table (mm)	distance between certical columns (mm)	Throat depth (mm)	Stroke (mm)	Max. Open height (mm)	Adjustment of stroke (mm)	Motor power (kW)	Net weight (kg)	Dimensions (L*W*H) (mm)
W67Y-30/1320	300	1320	1140	200	80	320	60	3	2000	1950*1420*2100
W67Y-30/1600	300	1600	1420	200	80	320	60	3	2300	2280*1500*2100
W67Y-40/1320	400	1320	1120	200	100	340	80	4	2200	1950*1420*2100
W67Y-40/1600	400	1600	1400	200	100	340	80	4	3100	2150*1500*2100
W67Y-40/2000	400	2000	1800	200	100	340	80	4	3300	2550*1500*2200
W67Y-40/2500	400	2500	2300	200	100	340	80	4	3600	3100*1500*2200
W67Y-63/2500	630	2500	2260	250	100	355	80	5.5	4800	3100*1600*2280
W67Y-63/3200	630	3200	2960	250	100	355	80	5.5	5600	3800*1650*2280
W67Y-80/2500	800	2500	2240	250	100	355	80	7.5	5900	3100*1650*2300
W67Y-80/3200	800	3200	2940	250	100	355	80	7.5	6600	3900*1700*2300
W67Y-80/4000	800	4000	3740	250	100	355	80	7.5	7800	4700*1600*2300
W67Y-100/2500	1000	2500	2210	320	120	415	100	7.5	7300	3200*1700*2560
W67Y-100/3200	1000	3200	2910	320	120	415	100	7.5	8100	3900*1800*2560
W67Y-100/4000	1000	4000	3710	320	120	415	100	7.5	9200	4700*1900*2560
W67Y-125/2500	1250	2500	2210	320	120	415	100	7.5	6500	3200*1700*2560
W67Y-125/3200	1250	3200	2910	320	120	415	100	7.5	8150	3900*1800*2560
W67Y-125/4000	1250	4000	3710	320	120	415	100	7.5	9800	4700*1900*2560
W67Y-160/3200	1600	3200	2830	320	200	455	160	11	12000	6700*2180*2700
W67Y-160/4000	1600	4000	3640	320	200	455	160	11	14000	4700*2200*2580
W67Y-160/6000	1600	6000	5630	320	200	455	160	11	19500	6700*2200*2900
W67Y-200/3200	2000	3200	2800	320	200	455	160	15	14500	3900*2200*2850
W67Y-200/4000	2000	4000	3600	320	200	455	160	15	15400	4800*2180*3000
W67Y-200/6000	2000	6000	5600	320	200	455	160	15	24600	6800*2200*3000
W67Y-250/3200	2500	3200	2850	400	250	560	200	18.5	16000	3900*2280*2900
W67Y-250/4000	2500	4000	3650	400	250	560	200	18.5	18800	4400*2280*3000
W67Y-250/6000	2500	6000	5650	400	250	560	200	22	28800	6800*2200*3600
W67Y-300/3200	3000	3200	2720	400	250	560	200	22	22800	3800*2200*3200
W67Y-300/4000	3000	4000	3520	400	250	560	200	22	24900	4600*2200*3200
W67Y-300/6000	3000	6000	5520	400	250	560	200	30	32000	6800*2200*3600
W67Y-400/3200	4000	3200	2800	400	320	630	270	30	24000	3800*2500*3450
W67Y-400/4000	4000	4000	3600	400	320	630	270	30	30000	4500*2500*3450